

SERIES: PACH-1500-15L Air Powered Hydraulic Pump



REDUCED DOWNTIME

PAXX air powered pumps have over 50 years history of use in the most demanding of environments. Proven, safe and very reliable.

TensionPro Air powered hydraulic pumps have been optimised to be perfect for pressurising hydraulic bolt tensioners. They are also suitable for with all high pressure hydraulic systems such as hydraulic jacks, pressure and hydro testing.

Model PAHF-1500-15L is the standard option for the SUB Subsea Tensioner Range. It incorporates a stainless steel tank and frame, and has a 15L tank to allow sufficient oil volume to use multiple tools and longer lengths of downline.

COMPACT DESIGN

- 670 x 340 x 513 mm compact size
- Stainless steel frame
- Dual scale pressure gauge
- Air silence included = 85 dBA max
- 15L tank
- ISO 10,32,46 oil compatible

Part Number	Flow Rate	Max Working Pressure		Piston Volume cc/stroke	Pressure Ratio	Gauge Scale		Weight kg
		bar	psi			bar	psi	
PACH-1500-15L	High	1500	21,750	4.5	323:1	0-2000	0-30,000	28

SAFE AND RELIABLE

- CE marked
- Pneumatic filter/regulator/lubricator included
- Pressure test certification
- Gauge calibration
- Full colour operating and safety manual
- High Cycle/long life performance
- 50° max operating temperature
- Air pressure safety relief valve
- Quick Connect Coupling Outlet
- Outlet pressure regulator

QUALITY SUPPORT AND SERVICE

Pumps are supplied with comprehensive operating manuals, pressure test and gauge calibration certificates. 24 hr telephone support.

Optional Extras

- ATEX ATEX Certified
- PT Digital Pressure Transducer
- CRO Chart Recorder Outlet
- TWIN Twin Port Outlet