




SERIES: FQXX Quick Connect Fittings



FQXX Quick Connect Fittings are used with all TensionPro hydraulic tensioners, nuts, hose and pumps.

They are designed to give non-drip connections, with simple and clean, positive connection and disconnection ensuring quick and reliable assembly of the hydraulic circuit.

A safety lock comes as standard for the 1000 bar and 1500 bar variants, which adds an extra layer of safety by eliminating any risks of accidental disconnections.

Part Numbers			
Nipple (Male) Quick Connect	FQCN-115-1000	FQCN-116-1500	FQCN-125-2500
Coupling (Female) Quick Connect	FQCC-115-1000	FQCC-116-1500	FQCC-125-2500
			
Part Numbers			
Min Burst Pressure	2600 bar	3000 bar	5000 bar
Nominal Flow Diameter	2.5 mm	2.5 mm	2.5 mm
Flow Capacity	6 l/min	6 l/min	5.8 l/min
Part Material	Hardened, zinc chromate plated steel	Hardened, zinc chromate plated steel	Hardened, zinc-nickel
Seal Material	Nitrile (NBR)	Nitrile (NBR)	Nitrile (NBR)
Temperature Range	-30°C +100°C	-30°C +100°C	-30°C +100°C

NEW LOCKING COLLARS NOW STANDARD FOR 1000 BAR AND 1500 BAR RANGE

